

INTEGR8 NON STRUCTURAL SR2 SECURITY SHUTTER



CERTIFIED PROTECTION AGAINST:



Forced Entry: Bodily Force Mitigation of opportunist intruder attempts using manual or bodily force including tools.



Forced Entry: Power Tools Protecting against deliberate forced entry of premises using mechanically-enhanced power tools.

PRODUCT REFERENCE

Integr8 Non Structural SR2 Security Shutter

PERFORMANCE

High strength extruded aluminium to ensure glazing and building protection.

CONCEALED SHUTTER

Specified to mitigate opportunist attack using bodily physical force and a selection of attack tools that increase mechanical advantage.

Installed in line with police approved standards. Compliant with new building guidelines.

The Integr8 Non Structural SR2 Shutter is an independently tested and certified product to LPCB 1175, Issue 7. Tested under the stringent Loss Prevention Standard to security rating 2 (SR2) the shutter system is recognised by Secured by Design as a police preferred specification.

SBD shutters certified to SR2 are rigorously tested to simulate an attack by a determined opportunist attacker in areas of high domestic risk, using bodily force and tools of a high mechanical advantage. The Integr8 Non Structural SR2 Shutter is for properties that do not require a structural lintel but necessitates integrated security with a flush finish.

LOCKDOWN TECHNOLOGY

No auxiliary locking required, manual or electronic.

Unique profiles lock shutter in any stop position - fully closed or otherwise.

Allows external first point-of-entry through the shutter.

INTEGR8 NON STRUCTURAL SR2 SECURITY SHUTTER

Manufactured completely to client and/or project preference, both the lath profile and side guides are polyester powder coated and can be customised to any RAL/BS colour. The finished product is a stunning security solution that enhances that unique architectural flair of the property.

SHUTTER CURTAIN

Compact high security Grade 6063 T6.
Finish as delivered: polyester powder coated in standard RAL/BS code.
Marine Grade PPC or anodising options including wood grain effect available.
Perforated laths available up to 13%.

HOOD BOX

Two part roll folded aluminium hood box with detachable front cover for maintenance.

BOTTOM RAIL

Reinforced extruded aluminium section with strengthened core.

FRAMES/GUIDES

Recessed into cavity of external wall complete with fully insulated closer.
Finish as delivered: polyester powder coated in standard RAL/BS colour.

SUITABLE SUBSTRATES:

Suitable for installation onto:

- Brickwork
- Blockwork
- Timber frame
- Structural Steel framing

SPECIFICATION

Specified to guard against an opportunist attack using bodily physical force and a selection of attack tools that increase mechanical advantage.

SUITABLE APPLICATIONS:

- Commercial
- Community
- Education
- Healthcare

ARRANGEMENT

Horizontal shutters, with roller shutter boxes mounted at high level to internal skin framing system.

CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or integration into existing building management systems and third party alarm.
Safety on close as assessment directs.

OPERATION

Motorised to allow controlled ascent and descent.
240v - Low duty cycle or where limited to single phase supply.
Manual override option for power failure.

