

OBEXION LPS 1175 SR2 CERTIFIED SECURITY SHUTTER

610 ROLLER SHUTTERS TO SPECIFIED OPENINGS

Manufacturer: Charter Global Ltd, Innovation House, Boulton Road, Reading, RG2 0NH. Tel: 0845 050 8705. Fax: 0845 050 8707. Website: www.charter-global.com/obexion/

Product Reference: Obexion SR2

Performance Criteria: Certified to LPS1175 issue 7. Security Rating 2 (SR2)

Arrangement: Horizontal shutters, with roller shutter boxes mounted at high level.

Shutter Curtain: SR2 tested extruded aluminium profiles with lockdown technology.

- Finish as Delivered: Polyester powder coated to 25 microns in Standard RAL/BS code.

Frame/Guides: Heavy duty extruded aluminium guides with double profile locking seals.

- Finish as Delivered: Polyester powder coated to 25 microns in Standard RAL/BS code.

Shutter Headbox: Two part roll formed aluminium section.

- Finish as Delivered: Polyester powder coated to 25 microns in Standard RAL/BS code.

Operation: 240v motor to allow controlled ascent and descent. Safety brake to avoid uncontrolled descent. Manual override facility is available as an option.

Ironmongery: Standard operation from key or push button switch. Integration with third party controls and alarms is possible – please consult manufacturer for further details.

Structure: Must be secured directly to structural steel, high density concrete block or brick.

Fixings: In accordance with manufacturers recommendations and details.

Other Requirements: It is a requirement of the system that the shutter must enter locked state automatically on closing without the need for ancillary locking.