

OBEXION UD SR3 SECURITY SHUTTER SYSTEM

610 ROLLER SHUTTERS TO SPECIFIED OPENINGS

Manufacturer: Charter Global Ltd, 1 Darwin Close, Reading, RG2 OTB. Tel: 0845 050 8705.

Fax: 0845 050 8707. Website: www.charter-global.com/obexion/

Product Reference: Obexion UD SR3 Security Shutter System

Performance: Product tested to comply with LPS 1175 issue 7, security rating three (SR3).

Arrangement: Horizontal shutters, with roller shutter boxes mounted at high level.

Shutter Curtain: Ultra DUO extruded aluminium lath profile to grade 6063 T6, certified to LPS 1175 issue 7, security rating three [SR3]

- Finish as Delivered: Polyester powder coated to 25 microns in Standard RAL/BS code.

Frame/Guides: Heavy duty extruded aluminium guide profiles to grade 6063 T6, with composite material seal, certified to LPS 1175 issue 7, security rating three (SR3).

- Finish as Delivered: Polyester powder coated to 25 microns in Standard RAL/BS code.

Bottom Rail: Reinforced bottom rail to grade 6063 T6 with integral rubber seal to base, certified to LPS 1175 issue 7, security rating three (SR3).

- Finish as Delivered: Polyester powder coated to 25 microns in Standard RAL/BS code

Operation: Motorised to allow controlled ascent and descent. Shutter to automatically lock into position upon descent without manual intervention or key locking.

Suitable Substrate: to be mechanically anchored directly to structural steel or masonry substrate as certified to LPS 1175 issue 7, security rating three (SR3).

Controls: As agreed with manufacturer.